



アンダル / Stainless Steel Angle Bar

SUS 304

寸 法 Dimension	長 さ (mm) Length			辺の許容差 Width Tolerance	厚さの許容差 Thickness Tolerance
	4000	5000	6000		
3 × 20	3.58	4.47	5.36	± 1.5	± 0.4
3 × 25	4.52	5.65	6.78	± 1.5	± 0.5
3 × 30	5.48	6.85	8.22	± 2.0	± 0.5
3 × 40	7.40	9.25	11.1	± 2.0	± 0.6
3 × 50	9.48	11.8	14.2	± 2.0	± 0.6
4 × 40	9.64	12.2	14.5	± 2.0	± 0.6
4 × 50	12.4	15.5	18.5	± 2.0	± 0.6
5 × 30	8.70		13.1	± 2.0	± 0.5
5 × 40	11.9	14.9	17.9	± 2.0	± 0.6
5 × 50	15.3	19.1	22.9	± 2.0	± 0.6
6 × 30		15.2		± 2.0	± 0.6
6 × 50	17.9	22.4	26.9	± 2.0	± 0.6
6 × 60		32.6		± 3.0	± 0.6
6 × 65	23.9	29.9	35.8	± 3.0	± 0.6

(mm)

(kg/本)

(mm)

(mm)

(kg/pc.)

は切断可能品 / :also available for cutting




アンダル / Stainless Steel Angle Bar

SUS 304

寸 法 Dimension	長 さ (mm) Length			辺の許容差 Width Tolerance	厚さの許容差 Thickness Tolerance
	4000	5000	6000		
6 × 75	27.7	34.6	41.5	± 3.0	± 0.7
6 × 100	37.3	46.6	55.9	± 3.0	± 0.7
7 × 70		44.5		± 3.0	± 0.7
8 × 80		57.8		± 3.0	± 0.7
8 × 100	48.8		73.2	± 3.0	± 0.7
9 × 75	40.4	50.5	60.6	± 3.0	± 0.7
9 × 90	49.2		73.8	± 3.0	± 0.7
10 × 100	60.4	75.5	90.6	± 4.0	± 0.8

(mm) (kg/本) (mm) (kg/pc.)

は切断可能品 / :also available for cutting

直角度 / Squareness $90^\circ \pm 2^\circ$ 曲がり / Straightness 長さ1mにつき3mm以下とし、全長に対しては、 $3\text{mm} \times \text{長さ(m)} \div 1\text{m}$ 以下とする。Not more than 3mm per 1m, Not more than $3\text{mm} \times \text{Length(m)} / 1\text{m}$ per Total Length.

長さ / Length +40mm, -0