



アンダル / Stainless Steel Angle Bar

SUS316

寸 法 Dimension	長 さ (mm) Length			辺の許容差 Width Tolerance	厚さの許容差 Thickness Tolerance
	4000	5000	6000		
3× 20	3.60			±1.5	±0.4
3× 25	4.56			±1.5	±0.5
3× 30		8.28		±2.0	±0.5
3× 40		11.2		±2.0	±0.6
4× 50		18.7		±2.0	±0.6
5× 40		18.0		±2.0	±0.6
6× 50		27.0		±2.0	±0.6
6× 65		36.1		±3.0	±0.6
6× 75		41.8		±3.0	±0.7
9× 75		60.6		±3.0	±0.7
10× 100		91.2		±4.0	±0.8

(mm)


(kg/本)

(mm)

(mm)

(kg/pc.)

は切断可能品 / :also available for cutting

直角度 / Squareness $90^\circ \pm 2^\circ$ 曲がり / Straightness 長さ1mにつき3mm以下とし、全長に対しては、 $3\text{mm} \times \text{長さ(m)} \div 1\text{m}$ 以下とする。Not more than 3mm per 1m, Not more than $3\text{mm} \times \text{Length(m)} / 1\text{m}$ per Total Length.

長さ / Length +40mm, -0