



耐熱ニッケル合金丸棒 / High Nickel Alloy for Heat Resistance

N 0 8 8 1 1 (ASTM B409/ASME SB409 UNS N08811)

ピーリング仕上げ / Peeled Surface Round Bar

| 外 径 O.D. | 長 さ 4000mm |
|-------------|---------------|
| 25 | 3.9 |
| 30 | 5.68 |
| 35 | 7.72 |
| 38 | 9.09 |
| 40 | 10.1 |
| 50 | 15.7 |
| 55 | 19.1 |
| 60 | 22.6 |
| 65 | 26.5 |
| 70 | 30.7 |
| 75 | 35.3 |
| 80 | 40.1 |
| 85 | 45.3 |
| 90 | 50.7 |
| 100 | 64.2 |
| 110 | 77.5 |

(mm)

(kg/m)

は切断可能品 / :also available for cutting



耐熱ニッケル合金丸棒 / High Nickel Alloy for Heat Resistance

N 0 8 8 1 1 (ASTM B409/ASME SB409 UNS N08811)

ピーリング仕上げ / Peeled Surface Round Bar

| 外 径 O.D. | 長 さ 4000mm |
|-------------|---------------|
| 120 | 92.0 |
| 130 | 108.0 |
| 140 | 125.0 |
| 200 | 253.0 |

(mm)

(kg/m)

は切断可能品 / :also available for cutting