



耐熱ニッケル合金丸棒 / High Nickel Alloy for Heat Resistance

N 0 6 6 0 0 (ASTM B168/ASME SB168 UNS N06600)

ピーリング仕上げ / Peeled Surface Round Bar

外 径 O.D.	長さ / Length 4000mm
16	1.7
18	2.1
19	2.4
22	3.22
25	4.16
30	6.06
35	8.1
36	8.72
38	9.5
40	10.8
45	13.4
50	16.8
55	20.0
60	24.1
65	27.9
(mm)	(kg/m)

外 径 O.D.	長さ / Length 4000mm
70	32.8
75	37.1
80	42.8
85	47.7
90	54.1
100	66.0
110	82.7
120	95.1
130	115.0
140	129.4
150	153.0
160	169.0
180	213.9
200	270.0
230	349.2
(mm)	(kg/m)

は切断可能品 / :also available for cutting



耐熱ニッケル合金丸棒 / High Nickel Alloy for Heat Resistance

N 0 6 6 0 0 (ASTM B168/ASME SB168 UNS N06600)

ピーリング仕上げ / Peeled Surface Round Bar

外 径 O.D.	長さ / Length 4000mm
250	421.0
(mm)	(kg/m)

外 径 O.D.	長さ / Length 4000mm
(mm)	(kg/m)

は切断可能品 / :also available for cutting