



六角棒 / Stainless Steel Hexagonal Bar

SUS304

スキnpas仕上げ / Skin-pass Surface

対辺 Size	長さ Length 2000mm	長さ Length 4000mm	寸法公差 (h12) O.D. Tolerance "h12"
5	0.17		+0, -0.12
6	0.25		+0, -0.12
7	0.34		+0, -0.15
8		0.44	+0, -0.15
10		0.69	+0, -0.15
12		0.99	+0, -0.18
13		1.16	+0, -0.18
14		1.35	+0, -0.18
17		1.98	+0, -0.18
19		2.48	+0, -0.21
21		3.03	+0, -0.21
22		3.32	+0, -0.21
23		3.63	+0, -0.21
24		3.96	+0, -0.21

(mm) (kg/m) (kg/m) (mm)

対辺 Size	長さ Length 2000mm	長さ Length 4000mm	寸法公差 (h12) O.D. Tolerance "h12"
26		4.64	+0, -0.21
27		5.01	+0, -0.21
29		5.78	+0, -0.21
30		6.18	+0, -0.21
32		7.03	+0, -0.25
35		8.41	+0, -0.25
36		8.90	+0, -0.25
38		9.92	+0, -0.25
41		11.5	+0, -0.25
46		14.5	+0, -0.25
50		17.2	+0, -0.25
54		20.0	+0, -0.30
55		20.8	+0, -0.30

(mm) (kg/m) (kg/m) (mm)

は切断可能品 / :also available for cutting



六角棒 / Stainless Steel Hexagonal Bar

SUS304

酸洗仕上げ / Pickled Surface

対 辺 Size	長 さ Length 4000mm	寸法公差 (h13) O.D. Tolerance "h13"
58	23.1	+0, -0.46
60	24.7	+0, -0.46
65	29.0	+0, -0.46
(mm)	(kg/m)	(mm)

対 辺 Size	長 さ Length 4000mm	寸法公差 (h13) O.D. Tolerance "h13"
70	33.7	+0, -0.46
75	38.6	+0, -0.46
80	44.0	+0, -0.54
(mm)	(kg/m)	(mm)

は切断可能品 / :also available for cutting